



## **Material Safety Data Sheet**

**Date: June, 22<sup>nd</sup> 2007**

<b>Identification</b> : M1300 Flexible Nylon	
<b>1. Company</b> : Dymo bvba Industriepark Noord 30 9100 St-Niklaas Belgium Telephone : +32 (03) 778 85 11 Fax : +32 (03) 776 51 81	
<b>2. Composition – Hazardous components</b>	
Polyamide fiber	CAS No. registered
Polyamide resin	registered
Acrylic adhesive	registered
<b>3. Physical/chemical Properties</b>	
Boiling point : N/A Specific gravity : no data Vapour pressure : N/A Melting point : about 220°C Solubility in water : N/A Appearance and odour : nylon coated fabric white colour, no odour	
<b>4. Fire and explosion hazard information</b>	
Flash point : N/A Extinguishing media : water mist, foam, dry powder, CO <sub>2</sub> gas Special fire fighting procedures : N/A Unusual fire and explosion hazards : N/A	
<b>5. Reactivity data</b>	
Stability : stable Conditions to avoid : N/A Incompatibility (material to avoid) : none Hazardous decomposition or byproducts : none Hazardous polymerization : will not occur	

**6. Health hazards**

Routes of entry : inhalation : no

skin : no

Ingestion : yes

Health hazard (acute/chronic) : N/A

Carcinogenicity : no

Emergency and first aid procedures : N/A

Medical conditions generally aggravated by exposure : will not occur

**7. Handling and Storage**

Steps to be taken in case material is released or spilled : N/A

Waste disposal method : used tape should be disposed of in environmentally safe manner and in accordance with governmental regulations

Storage : in a cool, dry and dark place

**8. Exposure controls/personal protection**

Ventilation: none

Special requirements : none

Protective gloves : none

Other personal protective clothing or equipment : none

Work/hygienic practises : none